


Anwendung / Application



ExpressCard SATA 2 Controller mit 2 Ports



ExpressCard SATA 2 Controller with 2 ports

Beschreibung

Der EX-3591 ist ein leistungsfähiger Serial-ATA 2 Controller mit der neuen ExpressCard Technologie. Er hat zwei Serial-ATA 2 Ausgänge für 2 x Serial-ATA Festplatten (einer pro Anschluss). Er ist die richtige Lösung um Serial-ATA Geräte an einen ExpressCard Slot anzuschließen. Mit der EX-3591 wird ein ExpressCard Kit 34/54mm (EX-10000) mitgeliefert der die ExpressCard seitlich in einem 54mm Slot stabilisiert.

Description

The EX-3591 is an increasingly powerful Serial-ATA 2 controller with the new ExpressCard technology. The EX-3591 has two Serial-ATA 2 ports for 2 x Serial-ATA hard disks, one per connection. He is the right solution to connect about Serial-ATA devices such a enclosure to an ExpressCard slot. With the EX-3591 it's included a ExpressCard Kit 34/54mm (EX-10000) what give the ExpressCard a lateral stability.

Merkmale

- Voll ExpressCard Standard 2.0 Kompatibel
- Kompatibel zu SATA Festplatten
- Befehls Mode Legacy Command Queuing (LCQ) und Native Command Queuing (NCQ)
- Unterstützt Festplatten über 137GB

Features

- Fully ExpressCard Standard 2.0 Compliant
- Compatible to SATA drives
- Supports Legacy Command Queuing (LCQ) and Native Command Queuing (NCQ)
- Support hard drive over 137GB

Spezifikationen

• Chip-Set:	Silicon Image SIL-3132
• Datentransfer-Rate:	eSATA 2 bis 3.0Gb/s (300MB/Sec.)
• Anschlüsse:	2 x Externe 7 Pin eSATA 2
• Hardwaresysteme:	ExpressCard Slot 34mm
• Treiber:	Windows 2000/XP(32&64bit)/Vista(32&64bit) Server(2000,2003 & 2008)/Win7(32&64bit), MAC OS
• Betriebstemperatur :	0 ⁰ bis 55 ⁰ Celsius
• Lagertemperatur:	-40 ⁰ bis 75 ⁰ Celsius
• Rel. Luftfeuchtigkeit:	5% bis 95%
• Abmessung:	130 x 34 mm
• Gewicht:	200g
• Lieferumfang:	EX-3591, ExpressCard Kit EX-10000, Treiber CD, Handbuch

Specifications

• Chip-Set:	Silicon Image SIL-3132
• Data transfer rate:	eSATA 2 up to 3.0Gb/s (300MB/Sec.)
• Connectors:	2 x External 7 pin eSATA 2
• Hardware system:	ExpressCard slot 34mm
• Driver:	Windows 2000/XP(32&64bit)/Vista(32&64bit) Server(2000,2003 & 2008)/Win7(32&64bit), MAC OS
• Operating Temperature :	32 ⁰ up to 131 ⁰ Fahrenheit
• Storage Temperature:	-40 ⁰ up to 167 ⁰ Fahrenheit
• Rel. Humidity:	5% to 95%
• Size:	115 x 48 mm
• Weight:	200g
• Packaging contents:	EX-3591, ExpressCard Kit EX-10000, Driver CD, Manual

System / OS



Geprüft / Approved



Verpackung / Packaging

