


Anwendung / Application



EX-10000
Inklusive/Included
ExpressCard Kit



ExpressCard eSATA 3 Controller mit 2 Ports



ExpressCard eSATA 3 Controller with 2 ports

Beschreibung

Der EX-3595 ExpressCard Controller stellt zwei externe SATA 3 Ports zur Verfügung. Er ist entwickelt worden um zwei weitere eSATA 3 High-Speeds Ports für Notebooks über den ExpressCard Bus zu erweitern um externe SATA 2 oder 3 Geräte wie zum Beispiel externe Festplatten Gehäuse. Der SATA 3 Bus Speed ist bis 6.0Gb/Sek. Der EX-3595 stellt eine richtige schnelle I/O Lösung zur Verfügung um dem Anwender die Möglichkeit zu geben schnelle Peripherie-Geräte anzuschließen.

Description

The EX-3595 ExpressCard controller provides a reliable solution for Notebook connect SATA 2 and 3 peripherals via the ExpressCard Bus. The SATA 3 bus speed is up to 6.0Gb/s. SATA 3 is a high-speed serial link and it replaces the parallel ATA standard. It is the right choice to connect SATA 3 devices to the ExpressCard Bus.

Merkmale

- Voll ExpressCard Standard 2.0 Kompatibel
- SATA 3 Controller Baustein für zwei SATA 3 Channels
- Kompatibel zu SATA und SATA 2 Festplatten
- Unterstützt SATA 3 Übertragungsraten von bis zu 6.0Gb/Sek.
- Unterstützt Legacy (LCQ) und Native (NCQ) Command Queuing
- Unterstützt Festplatten größer als 2TB

Features

- Fully ExpressCard Standard 2.0 Compliant
- SATA 3 Controller Chip for dual SATA 3 Channels
- Backward Compatible with SATA2/SATA Devices
- Supports SATA 3 transfer rate of 6.0Gb/s.
- Support Legacy (LCQ) and Native (NCQ) Command Queuing
- Support hard drives greater than 2TB

Spezifikationen

• Chip-Set:	Marvell 88SE9128
• Datentransfer-Rate:	bis zu 6.0Gb/Sek.
• Anschlüsse:	2 x 7 Pin eSATA 3
• Hardwaresysteme:	ExpressCard 34mm Slot
• Treiber:	Windows 2000/XP/2003/Vista/Win 7
• Betriebstemperatur :	0° bis 55° Celsius
• Lagertemperatur:	-40° bis 75° Celsius
• Rel. Luftfeuchtigkeit:	5% bis 95%
• Abmessung:	112 x 34 mm
• Gewicht:	200g
• Lieferumfang:	EX-3595, Treiber CD, Handbuch

Specifications

• Chip-Set:	Marvell 88SE9128
• Data transfer rate:	up to 6.0Gb/Sec.
• Connector:	2 x 7 pin eSATA 3
• Hardware system:	ExpressCard 34mm Slot
• Driver:	Windows 2000/XP/2003/Vista/Win 7
• Operating Temp. :	32 ⁰ up to 131 ⁰ Fahrenheit
• Storage Temp.:	-40 ⁰ up to 167 ⁰ Fahrenheit
• Rel. Humidity:	5% up to 95%
• Size:	112 x 34 mm
• Weight:	200g
• Packaging contents:	EX-3595, Driver CD, Manual

System / OS



Geprüft / Approved



Verpackung / Packaging

